

# Compact Roundflow Cassette

FCQ-C8 / RZQ-D(B9W1)



The unique 360° radial air pattern ensures uniform air flow and temperature distribution. The slim FCQ-C model has a low installation height, perfect for applications in restricted false ceilings and, achieves a high level of energy efficiency.

Height	204mm
Width	840mm
Depth	840mm



FCQ71C8

Height	770mm
Width	900mm
Depth	320mm



RZQ71D

See tables overleaf for full list of dimensions

- **RZQ Seasonal Inverter technology:** first light commercial range in the market optimised for Seasonal Efficiency. Takes account of multiple cooling/heating temperatures as well as unit operation at partial load instead of just full capacity. Will also consider the power consumed by equipment in auxiliary mode (thermostat off, standby mode, OFF mode).
- **Application flexibility:** Comms, computer and server room cooling possible. Also suitable for use in R-22 replacement projects.
- **Wired remote controller:** provides a 7-day schedule timer, enabling the user to program the air conditioning daily or weekly, with up to 5 different actions per day possible (BRC1D52 standard / BRC1E51A optional).
- **BRC1E51A – New optional wired controller:** allows easy navigation through menu items, via a personalised display.
- **Self-cleaning panel (available as accessory):** Maintenance time and costs and energy consumption reduced. It is equipped with a special rounded filter, which automatically cleans itself once a day. The dust from this filter is stored in the indoor unit and can be removed with a normal vacuum cleaner.
- **Air flow flexibility:** a wide selection of 23 different airflow patterns enables unit installation in corners or small rooms.
- **Home Leave operation:** automatically keeps the room temperature at a specified favourite comfort level.
- **Horizontal air discharge:** ensures draught free operation and prevents ceiling soiling.
- **Air purification filter:** removes airborne dust particles to ensure a steady supply of clean air.
- **Self diagnosis digital display:** in the unlikely event that an abnormality occurs, the LCD remote controller displays the error code allowing prompt maintenance.
- **Auto-restart function:** after a power failure in the building, the system automatically restarts to the setting in operation before the power failure.

**ENERGY LABEL:  
UP TO CLASS  
A**

# HEAT PUMP

# SEASONAL INVERTER

Indoor Units				FCQ71C8	FCQ100C8		FCQ125C8		FCQ140C8	
Capacity	Cooling capacity	Standard	kW	7.1	10.0		12.5		14.0	
	Heating capacity	Standard	kW	8.0	11.2		14.0		16.0	
Nominal	EER / COP	Cooling / Heating		3.36 / 3.62	3.79 / 3.78	3.79 / 3.57	3.38 / 3.61	3.22 / 3.21	2.74 / 3.27	2.61 / 2.81
	Annual energy consumption	kWh		1055	1319	1320	1850	1940	2555	2680
	Energy Label	Cooling / Heating		A / A	A / A	A / B	A / B	A / C	D / C	D / D
Seasonal (*)	SEER / SCOP	Cooling / Heating		3.71 / -	3.54 / -	3.56 / -	3.73 / -	3.58 / -	3.14 / -	3.01 / -
Dimensions	(Height x Width x Depth)		mm	204x840x840		246x840x840				
Weight			kg	21	23					
Air Flow Rate	Cooling	High/Low	m <sup>3</sup> /min	15.5 / 9.0		23.5 / 16.0		27.5 / 19.0		
	Heating	High/Low	m <sup>3</sup> /min	16.0 / 9.5		23.5 / 16.0		27.5 / 19.0		
Sound Power	Cooling	High	dBA	51	54		58			
Sound Pressure	Cooling	High/Low	dBA	33 / 28		37 / 32		41 / 35		
	Heating	High/Low	dBA	34 / 28		37 / 32		41 / 35		42 / 35
Refrigerant			Type	R-410A						
Power Supply				1~/220-240V/50/60Hz						
Decoration Panel	Model	BYCQ140CW1 <sup>1</sup> / BYCQ140CW1W <sup>2</sup> / BYCQ140CGW1 <sup>3</sup>								
	Colour	Pure white (RAL 9010)								
	HxWxD	mm		50x950x950 / 50x950x950 / 130x950x950						
	Weight	kg		5.5 / 5.5 / 11.5						
Controller	Wired/Wireless			BRC1D52 (standard) / BRC7F532F (optional) BRC1E51A (optional)						
Outdoor Unit				RZQ71D3V1	RZQ100D9V1	RZQ100B9W1	RZQ125D9V1	RZQ125B9W1	RZQ140D9V1	RZQ140B9W1
Dimensions	(Height x Width x Depth)		mm	770x900x320	1345x900x320		1345x900x320		1345x900x320	
Weight			kg	67	108	106	108	106	108	106
Operation Range	Cooling	Min~Max	°CDB	-15.0~-50.0						
	Heating	Min~Max	°CWB	-20.0~-15.5						
Sound Power	Cooling		dBA	64	65		67	66	68	66
Sound Pressure (Standard)	Cooling		dBA	48	50		51	50	51	50
	Heating		dBA	50	52		53	52	53	52
Sound Level (Night quiet)		Sound Pressure	dBA	43	45				46	45
Refrigerant			Type	R-410A						
Power Supply				1~/220-240V/50Hz	1~/220-240V/50Hz	3N~/400V/50Hz	1~/220-240V/50Hz	3N~/400V/50Hz	1~/220-240V/50Hz	3N~/400V/50Hz
Piping connections	Liquid (OD)/Gas/Drain		mm	9.52 / 15.9 / 26						
Piping Length (Maximum)			m	50	75					
Max. internunit level difference			m	0.5						
Max installation height difference			m	30						

(\*) Seasonal efficiencies are calculated based on draft PrEn 14825: 2009 (under inquiry stage). Data are subject to change.

<sup>1</sup> Pure white standard panel with grey louvres; <sup>2</sup> Pure white standard panel with white louvres; <sup>3</sup> Pure white auto cleaning panel



Authorised User No. 02061

Visit [www.eca.gov.uk/etl](http://www.eca.gov.uk/etl) and type 'Daikin' in the quick search box for details of the latest ECA qualifying Daikin units

[www.daikin.co.uk](http://www.daikin.co.uk)

Daikin products are distributed by:



Daikin units comply with the European regulations that guarantee the safety of the product.

Daikin Europe N.V. participates in the Eurovent Certification Programme for Air Conditioners (AC), Liquid Chilling Packages (LCP) and Fan Coil Units (FC); the certified data of certified models are listed in the Eurovent Directory. Multi units are Eurovent certified for combinations up to 2 indoor units.

The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin UK. Daikin UK has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin UK explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin UK.