

Pair, Twin, Triple, double twin

Industry leading technology for commercial applications and technical rooms

- › Top efficiency:
 - energy labels up to A++ in both cooling and heating
 - compressor that offers substantial efficiency improvements
 - control logic that optimises efficiency at the most frequently encountered operating conditions and that optimises the auxiliary modes (when the unit is not active)
 - heat exchangers that optimise the refrigerant flow at the most frequent operating conditions (temperature and load)
 - via improved nominal performances
- › The perfect balance in efficiency and comfort thanks to Variable Refrigerant Temperature: top seasonal efficiency throughout most of the year and quick reaction speed on the hottest days.



- › Suits high sensible, infrastructure cooling applications
- › Replace existing R-22 or R-407C systems without having to replace the piping



RZQG100-125-140L9V1/L(8)Y1

- › Extended operation range down to -20°C in heating and down to -15°C in cooling
- › With a gas cooled PCB reliable cooling is guaranteed as it is not influenced by ambient temperature
- › Maximum piping length up to 75m, minimum piping length is 5m.

Comfort cooling combination table

	FCAHG-G				FCAG-A				FFA-A				FDA-A				FDM-F3				FBA-A				FHA-A				FAA-A				FUA-A				FNA-A				FVA-A					
capacity class	71	100	125	140	35	50	60	71	100	125	140	35	50	60	71	100	125	140	35	50	60	71	100	125	140	35	50	60	71	100	125	140	35	50	60	71	100	125	140							
RZQG71L9V1	RZQG71L8Y1							2				P				2				2				2			P				2				P				P							
RZQG100L9V1		P			3	2				P			3	2					3	2				3	2			P				3	2				P				P					
RZQG125L9V1			P		4	3	2				P		4	3	2	P			4	3	2	P			4	3	2		P				4	3	2			P				P				
RZQG140L9V1				P	4	3		2				P	4	3				P	4	3				P	4	3		2			P	2		2			P	2			4	3				P

P = application ; 2/3/4 = twin/triple/double twin application

Infrastructure cooling combination table



		FAA-A				FHA-A				FBA-A				FDXW-F3				FUA-A				FVA-A				FFA-A				FCAHG-G				FCAG-A				
		71	100	35	50	60	71	100	125	140	35	50	60	71	100	125	140	35	50	60	71	100	125	140	35	50	60	71	100	125	140	35	50	60	71	100	125	140
capacity class		71	100	35	50	60	71	100	125	140	35	50	60	71	100	125	140	35	50	60	71	100	125	140	35	50	60	71	100	125	140	35	50	60	71	100	125	140
RZQG71L9V1	RZQG71L8Y1		P	3	2			P			3	2			P			3	2			P			3	2			P			3	2			P		
RZQG100L9V1	RZQG100L8Y1	2		4	3		2			P	4	3		2			P	4	3		2			P	4	3		2			P	4	3		2			P
RZQG125L9V1	RZQG125L8Y1	2		4	3		2			P	4	3		2			P	4	3		2			P	4	3		2			P	4	3		2			P
RZQG140L9V1	RZQG140LY1	2		4	3		2			P	4	3		2			P	4	3		2			P	4	3		2			P	4	3		2			P

P = Pair, 2 = Twin, 3 = Triple, 4 = Double twin; For more information on infrastructure cooling options refer to infrastructure cooling catalogue.

Outdoor unit		RZQG		71L9V1	100L9V1	125L9V1	140L9V1	71L8Y1	100L8Y1	125L8Y1	140L8Y1
Dimensions	Unit	HeightxWidthxDepth	mm	990x940x320	1,430x940x320		990x940x320		1,430x940x320		
Weight	Unit		kg	69	95		80		101		
Sound power level	Cooling		dBA	64	66	67	69	64	66	67	69
Sound pressure level	Cooling	Nom.	dBA	48	50	51	52	48	50	51	52
	Heating	Nom.	dBA	50	52	53		50	52	53	
Operation range	Night quiet mode	Level 1	dBA	43	45		43		45		
	Cooling	Ambient	Min.~Max.	°CDB	-15~50		-15~50		-20~15.5		
Refrigerant	Heating	Ambient	Min.~Max.	°CWB	-20~15.5		-20~15.5		-20~15.5		
	Type			R-410A		R-410A		R-410A		R-410A	
Piping connections	Charge		kg	2.9	4.0		2.9		4.0		
			TCO _{2eq}	6.1	8.4		6.1		8.4		
Piping connections	GWP			2,087.5		2,087.5		2,087.5		2,087.5	
	Liquid	OD	mm	9.52		9.52		9.52		9.52	
Piping length	Gas	OD	mm	15.9		15.9		15.9		15.9	
	OU - IU	Max.	m	50	75		50		75		
Additional refrigerant charge	System	Equivalent	m	70	90		70		90		
	Chargeless		m	30		30		30		30	
Power supply	Level difference	IU - OU	Max.	30.0		30.0		30.0		30.0	
	Phase / Frequency / Voltage		Hz / V	1~ / 50 / 220-240		1~ / 50 / 220-240		3N~ / 50 / 380-415		3N~ / 50 / 380-415	
Current - 50Hz	Maximum fuse amps (MFA)		A	25	40		16		25		

(1) MFA is used to select the circuit breaker and the ground fault circuit interrupter (earth leakage circuit breaker). For more detailed information on each combination, please refer to the electrical data drawing.