

Type	Model name	Dry contact	Function				Specifications									
			Apply voltage	Operation/ Stop	Emergency stop	Forced Stop	Forced thermostat off	Terminal	Signal type	Terminal voltage	External power supply		Wire size	Maximum length of cable	Connector (service parts)	
											Allowable voltage	Allowable current				
Indoor unit	Compact Cassette	Dry contact	●(46-00)	●(46-01)	●(46-02)	-	CNA02 (PIN1-3)	Edge	DC12[V]	-	-	AWG22 Twist	150[m]	9368779023		
			-	-	-	●	CNA02 (Ch1:PIN1-3) (Ch2:PIN2-3)	Pulse #1		-	-			9368778019		
			-	-	-	●	CNA04 (PIN1-2)	Edge		-	-			9368779016		
		Apply voltage	●(46-00)	●(46-01)	●(46-02)	-	CNA01 (PIN1-3)	Edge	-	DC12-24[V]	10[mA] or less			9368778002		
			-	-	-	●	CNA01 (Ch1:PIN1-3) (Ch2:PIN2-3)	Pulse #1						-	-	9368779009
			-	-	-	●	CNA03 (PIN1-2)	Edge						-	-	9368779016
	Cassette	Dry contact	●(46-00)	●(46-01)	●(46-02)	-	CN17 (Ch1:PIN1-3)	Edge	DC12[V]	-	-	AWG22 Twist	150[m]	9368779023		
			-	-	-	●	CN17 (Ch1:PIN1-3) (Ch2:PIN2-3)	Pulse #1		-	-			9368778019		
			-	-	-	●	CN6 (PIN1-2)	Edge		-	-			9368779016		
		Apply voltage	●(46-00)	●(46-01)	●(46-02)	-	CN6 (Ch1:PIN1-2) (Ch2:PIN1-3)	Pulse #1	-	DC12-24[V]	5mA-10mA			9368778002		
			-	-	-	●	CN6 (PIN1-2)	Edge						-	-	9368779009
			-	-	-	●	CN6 (Ch1:PIN1-2) (Ch2:PIN1-3)	Pulse #1						-	-	9368779016
Low Static Pressure Duct	Dry contact	●(46-00)	●(46-01)	●(46-02)	-	CN27 (PIN1-3)	Edge	DC5.25[V]	-	-	AWG22 Twist	25[m]	9368779023			
		-	-	-	●	CN27 (Ch1:PIN1-3) (Ch2:PIN2-3)	Pulse #1		-	-			9368778019			
		-	-	-	●	CN27 (PIN1-3)	Edge		-	-			9368779016			
	Apply voltage	●(46-00)	●(46-01)	●(46-02)	-	CN27 (Ch1:PIN1-3) (Ch2:PIN2-3)	Pulse #1	-	DC12-24[V]	10[mA] or less			9368778002			
		-	-	-	●	CN27 (PIN1-3)	Edge						-	-	9368779009	
		-	-	-	●	CN27 (Ch1:PIN1-3) (Ch2:PIN2-3)	Pulse #1						-	-	9368779016	
Slim Duct	Dry contact	●(46-00)	●(46-01)	●(46-02)	-	CN27 (PIN1-3)	Edge	DC12[V]	-	-	AWG22 Twist	150[m]	9368779023			
		-	-	-	●	CN27 (Ch1:PIN1-3) (Ch2:PIN2-3)	Pulse #1		-	-			9368778019			
		-	-	-	●	CN27 (PIN1-3)	Edge		-	-			9368779016			
	Apply voltage	●(46-00)	●(46-01)	●(46-02)	-	CN27 (Ch1:PIN1-3) (Ch2:PIN2-3)	Pulse #1	-	DC12-24[V]	10[mA] or less			9368778002			
		-	-	-	●	CN27 (PIN1-3)	Edge						-	-	9368779009	
		-	-	-	●	CN27 (Ch1:PIN1-3) (Ch2:PIN2-3)	Pulse #1						-	-	9368779016	
Medium Static Pressure Duct	Dry contact	●(46-00)	●(46-01)	●(46-02)	-	CN27 (PIN1-3)	Edge	DC5.25[V]	-	-	AWG22 Twist	150[m]	9368779023			
		-	-	-	●	CN27 (Ch1:PIN1-3) (Ch2:PIN2-3)	Pulse #1		-	-			9368778019			
		-	-	-	●	CN27 (PIN1-3)	Edge		-	-			9368779016			
	Apply voltage	●(46-00)	●(46-01)	●(46-02)	-	CN27 (Ch1:PIN1-3) (Ch2:PIN2-3)	Pulse #1	-	DC12-24[V]	10[mA] or less			9368778002			
		-	-	-	●	CN27 (PIN1-3)	Edge						-	-	9368779009	
		-	-	-	●	CN27 (Ch1:PIN1-3) (Ch2:PIN2-3)	Pulse #1						-	-	9368779016	
High Static Pressure Duct	Dry contact	●(46-00)	●(46-01)	●(46-02)	-	CN27 (PIN1-3)	Edge	DC12[V]	-	-	AWG22 Twist	150[m]	9368779023			
		-	-	-	●	CN27 (Ch1:PIN1-3) (Ch2:PIN2-3)	Pulse #1		-	-			9368778019			
		-	-	-	●	CN27 (PIN1-3)	Edge		-	-			9368779016			
	Apply voltage	●(46-00)	●(46-01)	●(46-02)	-	CN27 (Ch1:PIN1-3) (Ch2:PIN2-3)	Pulse #1	-	DC12-24[V]	10[mA] or less			9368778002			
		-	-	-	●	CN27 (PIN1-3)	Edge						-	-	9368779009	
		-	-	-	●	CN27 (Ch1:PIN1-3) (Ch2:PIN2-3)	Pulse #1						-	-	9368779016	
Ceiling	Dry contact	●(46-00)	●(46-01)	●(46-02)	-	CN17 (Ch1:PIN1-3)	Edge	DC12[V]	-	-	AWG22 Twist	150[m]	9368779023			
		-	-	-	●	CN17 (Ch1:PIN1-3) (Ch2:PIN2-3)	Pulse #1		-	-			9368778019			
		-	-	-	●	CN6 (PIN1-2)	Edge		-	-			9368779016			
	Apply voltage	●(46-00)	●(46-01)	●(46-02)	-	CN6 (Ch1:PIN1-2) (Ch2:PIN1-3)	Pulse #1	-	DC12-24[V]	10[mA] or less			9368778002			
		-	-	-	●	CN6 (PIN1-2)	Edge						-	-	9368779009	
		-	-	-	●	CN6 (Ch1:PIN1-2) (Ch2:PIN1-3)	Pulse #1						-	-	9368779016	
Compact Wall Mounted	Dry contact	●(46-00)	●(46-01)	●(46-02)	-	CN9 (PIN1-3)	Edge	DC5.25[V]	-	-	AWG22 Twist	25[m]	9368779023			
		-	-	-	●	CN9 (Ch1:PIN1-2) (Ch2:PIN1-3)	Pulse #1		-	-			9368778019			
		-	-	-	●	CN9 (PIN1-3)	Edge		-	-			9368779016			
	Apply voltage	●(46-00)	●(46-01)	●(46-02)	-	CN9 (Ch1:PIN1-2) (Ch2:PIN1-3)	Pulse #1	-	DC12-24[V]	10[mA] or less			9368778002			
		-	-	-	●	CN9 (PIN1-3)	Edge						-	-	9368779009	
		-	-	-	●	CN9 (Ch1:PIN1-3) (Ch2:PIN2-3)	Pulse #1						-	-	9368779016	
Wall Mounted	Dry contact	●(46-00)	●(46-01)	●(46-02)	-	CN21 (PIN1-3)	Edge	DC5.25[V]	-	-	AWG22 Twist	25[m]	9368779023			
		-	-	-	●	CN21 (Ch1:PIN1-3) (Ch2:PIN2-3)	Pulse #1		-	-			9368778019			
		-	-	-	●	CN21 (PIN1-3)	Edge		-	-			9368779016			
	Apply voltage	●(46-00)	●(46-01)	●(46-02)	-	CN21 (Ch1:PIN1-3) (Ch2:PIN2-3)	Pulse #1	-	DC12-24[V]	10[mA] or less			9368778002			
		-	-	-	●	CN21 (PIN1-3)	Edge						-	-	9368779009	
		-	-	-	●	CN21 (Ch1:PIN1-3) (Ch2:PIN2-3)	Pulse #1						-	-	9368779016	

Note : For Selecting Relay, minimum permissible load must be less than 1(mA)

: When you use Apply voltage, Take "+" polarity for PIN1
: Number inside bracket "()" indicates Function number and Setting number.
: Expression "●" is equipping function.

*1 : Default setting is Edge signal, if you use pulse signal, must be set Dip SW2-2 to ON position.

*2 : Default setting is Edge signal, if you use pulse signal, must be set Dip SW3-4 to ON position.