

FTXA-C (W/S/B) / RXA-A/B (8) stylish



Stylish

Where innovation meets creativity

With its sleek white, black, or silver finish, this compact unit blends effortlessly into any interior. Advanced airflow technology and an intelligent thermal sensor ensure a perfectly balanced climate throughout the room, while near-silent operation keeps your space calm and undisturbed. And with Daikin's Flash Streamer technology, the air you breathe stays fresh, clean, and allergen-free — so you can relax, focus, or entertain in total comfort.

Refined design, effortlessly elegant

Crafted to suit the most stylish interiors, this unit combines sleek form with smart function. With a depth of less than 19 cm and a choice of white, black, or silver finishes, it blends seamlessly into any décor — whether in a sophisticated home or a high-end boutique. Its compact presence never intrudes, making it ideal for those who value both space and aesthetic harmony.

Subtle airflow, complete comfort

Thanks to the Coanda effect, airflow is gently guided along ceilings or walls, creating a soft, natural climate throughout the room. This ensures even temperature distribution, eliminating drafts and creating a space that feels consistently pleasant — whether you're hosting friends, unwinding at home, or welcoming customers into a serene setting.

Comfort that senses your needs

An intelligent thermal sensor reads the room's surface temperatures and intuitively adjusts the airflow to match. It begins by evenly spreading air throughout the space, then shifts to target specific zones that need heating or cooling. The result? A perfectly balanced environment that feels tailored to your daily rhythms — without you lifting a finger.

Breathe well, live well

Daikin's Flash Streamer technology purifies your air continuously, breaking down allergens and odours at a molecular level. Whether it's pollen, pet dander, or lingering smells, the result is a fresher, cleaner space where you can breathe freely — ideal for homes focused on wellness and shops that care about customer comfort.

Daikin Onecta App

Control your air conditioning with your phone through Daikin's own Onecta App. Available on Apple and Android, control your system with ease, from anywhere. Enjoy easy voice control of your units by connecting Onecta to Google Home or Amazon Alexa.

Quiet by design

This unit is practically silent in operation — quieter than a soft whisper. It maintains the ideal indoor climate without interrupting your sleep, your thoughts, or your conversations, making it perfect for bedrooms, reading corners, and tranquil retail spaces alike.



FTXA-CW



FTXA-CB



FTXA-CS



RXA-A8/B8



ARC466A85



WI-FI ADAPTOR
INCLUDED AS STANDARD



FTXA-C (W/S/B) / RXA-A/B (8) stylish

R-32 BLUEEVOLUTION

| Indoor Units | White (RAL 9002) | | CTXA15CW | FTXA20CW | FTXA25CW | FTXA35CW | FTXA42CW | FTXA50CW |
|--|---------------------------|---------------------|------------------------------|------------------------|------------------------|------------------------|------------------------|-------------------------|
| | Black (RAL 9005) | | CTXA15CB | FTXA20CB | FTXA25CB | FTXA35CB | FTXA42CB | FTXA50CB |
| | Silver (RAL 9006) | | CTXA15CS | FTXA20CS | FTXA25CS | FTXA35CS | FTXA42CS | FTXA50CS |
| Capacity | UK Total Cooling | kW | Multi Combination Only | 1.95 | 2.44 | 3.32 | 4.11 | 4.89 |
| | UK Sensible Cooling | kW | | 1.95 | 1.96 | 2.43 | 3.01 | 3.56 |
| | Nominal Cooling | kW | | 2.0 | 2.5 | 3.4 | 4.2 | 5.0 |
| | Nominal Heating | kW | | 2.5 | 2.8 | 4.0 | 5.4 | 5.8 |
| Seasonal Efficiency (EN14825) COOLING | Energy Label | | | A+++ | A+++ | A+++ | A++ | A++ |
| | Pdesign | kW | | 2.0 | 2.5 | 3.4 | 4.2 | 5.0 |
| | SEER | | | 8.75 | 8.74 | 8.73 | 7.50 | 7.33 |
| | Annual Energy Consumption | kWh | | 80 | 101 | 136 | 196 | 239 |
| Seasonal Efficiency (EN14825) HEATING | Energy Label | | | A+++ | A+++ | A+++ | A++ | A++ |
| | Pdesign | kW | | 2.40 | 2.45 | 2.50 | 3.80 | 4.00 |
| | SCOP | | | 5.15 | 5.15 | 5.15 | 4.6 | 4.6 |
| | Annual Energy Consumption | kWh | | 652 | 666 | 680 | 1150 | 1217 |
| Air Flow Rate (Cooling) | High / Med / Low / Silent | m ³ /min | 11.0 / 8.2 / 6.1 / 4.6 | 11.0 / 8.2 / 6.1 / 4.6 | 11.5 / 8.6 / 6.1 / 4.6 | 11.9 / 8.6 / 6.1 / 4.6 | 13.1 / 9.8 / 7.2 / 4.6 | 13.5 / 10.4 / 7.6 / 5.2 |
| Dimensions | Height / Width / Depth | mm | 295 x 798 x 189 | 295 x 798 x 189 | 295 x 798 x 189 | 295 x 798 x 189 | 295 x 798 x 189 | 295 x 798 x 189 |
| Weight | | kg | 12 | 12 | 12 | 12 | 12 | |
| Sound Pressure (Cooling) | High / Med / Low / Silent | dBA | 39 / 32 / 25 / 21 | 39 / 32 / 25 / 19 | 40 / 33 / 25 / 19 | 41 / 33 / 25 / 19 | 45 / 37 / 29 / 21 | 46 / 39 / 31 / 24 |
| Sound Power (Cooling) | | dBA | 57 | 57 | 57 | 60 | 60 | 60 |

| Outdoor Units | | | RXA20A8 | RXA25A8 | RXA35A8 | RXA42B8 | RXA50B8 |
|---------------------------|-----------------------------|---------------------|-----------------------|-----------------------|-----------------------|-----------------------|------------------------|
| Dimensions | Height x Width x Depth | mm | 550 x 840 x 350 | 550 x 840 x 350 | 550 x 840 x 350 | 734 x 870 x 373 | 734 x 870 x 373 |
| Weight | | kg | 32 | 32 | 32 | 50 | 50 |
| Electrical Details | Power Supply | | 1ph | 1ph | 1ph | 1ph | 1ph |
| | Maximum Input Current (MCA) | A | 9.88 | 11.17 | 12.29 | 12.8 | 12.8 |
| | Max Fuse Size | A | 10 | 13 | 13 | 16 | 16 |
| | Interconnection Wiring | Core / Cable Size | 3+E / 1.5 | 3+E / 1.5 | 3+E / 1.5 | 3+E / 1.5 | 3+E / 1.5 |
| Piping Connections | Liquid / Gas | inches (mm) | 1/4 (6.4) / 3/8 (9.5) | 1/4 (6.4) / 3/8 (9.5) | 1/4 (6.4) / 3/8 (9.5) | 1/4 (6.4) / 3/8 (9.5) | 1/4 (6.4) / 1/2 (12.7) |
| Pipework | Maximum Length | m | 20 | 20 | 20 | 30 | 30 |
| | Maximum Vertical Rise | m | 15 | 15 | 15 | 20 | 20 |
| | Precharged to | m | 10 | 10 | 10 | 10 | 10 |
| | Additional charge | g/m | 20 | 20 | 20 | 20 | 20 |
| Sound Pressure (Cooling) | Nominal | dBA | 0.76 | 0.76 | 0.76 | 1.1 | 1.1 |
| | Holding charge | kg | 46 | 46 | 49 | 48 | 48 |
| Sound Power (Cooling) | | dBA | 59 | 59 | 61 | 62 | 62 |
| Operating Range (Cooling) | Min / Max | °CDB | -10 / 46 | -10 / 46 | -10 / 46 | -10 / 46 | -10 / 46 |
| Operating Range (Heating) | Min / Max | °CWB | -15 / 18 | -15 / 18 | -15 / 18 | -15 / 18 | -15 / 18 |
| Air Flow Rate (Cooling) | Nominal | m ³ /min | 34.0 | 34.0 | 36.0 | 46.6 | 46.6 |
| Meets ETL criteria | | | ● | ● | ● | ● | ● |

Accessories:

| Accessory Ref | Description |
|---------------|---|
| EKRS21 | Wire harness for new S21 port for all marked (*) options |
| BRC073* | Wired remote control – connection cable required |
| BRCW901A03 | 3m extension cord required for wired remote controller BRC073 |
| BRCW901A08 | 8m extension cord required for wired remote controller BRC073 |
| K.CGM | Condensing unit guard (1150 x 1150 x 650) |
| K.CG5 | Condensing unit guard (750 x 1050 x 460) |
| K.CWB90-2 | Wall bracket (90kg, 500mm support arm) |
| K.DT1 | Condensate drip tray for use with K.CWB90-2 |
| K.FF600S | Two flexi-feet (Standard 600mm x 185mm x 100mm) to mount the outdoor unit |
| KLIC-DDV3* | KNX interface for Split type systems |
| KRP413A15* | Adaptor PCB for remote on/off control – constant/pulse contact |
| KRP928A25* | Adaptor PCB for interface to Daikin centralised control systems |
| RTD-RA* | Adaptor PCB for Modbus connection and/or extended system functions |

Notes & Features:

- › All fan coils are supplied with infrared remote controller ARC466A85
- › Fan with Coanda effect for optimum air distribution and indoor comfort
- › Grid eye sensor redirects air away from the occupants in the room
- › Flash Streamer technology helps improve indoor air quality
- › Antibacterial Filter for effectively arresting small particulates

The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin UK. Daikin UK has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin UK explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin UK.



Daikin Europe N.V. participates in the Eurovent Certification programme for Air conditioners (AC), Liquid Chilling Packages (LCP), Air handling units (AHU) and Fan coil units (FCU). Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com